



See online
technical sheet

/ PRG3/C18-L182022

Pliers for MV cable outer sheath with 3 adjustable longitudinal cutting depth



/ Use

The pliers PRG3/C18-L182022 enables the user to make a circular and longitudinal cut in order to remove cable's outer sheath

All cutting depth ranging from 0,5 mm / 0,020 in to 5 mm / 0,197 in are available on demand
Maximum cutting depth for the cutting head with 3 positions : 3,5 mm / 0,138 in

/ Advantages

- Interchangeable head between the 3 plier sizes PR4, PRG3, PRG4
- Faster and safer than a knife
- Quick adjustment of the longitudinal cutting depth

/ Technical specifications

- Specific tools : Cable tools
- Cable tools : Cable tools
- For network cables : medium voltage
- Packaging : Carton box
- Weight (g) : 680
- Max diameter (mm) : 52
- Mini diameter (mm) : 26
- Circular cutting depth (mm) : 1.8

- Longitudinal cutting depth (mm) : 1,8 - 2,0 - 2,2
- Tools king : Specific tools

/ Spare parts

	Reference	Designation
	MTC3/18	Circular cutting wheel
	LGPG	Set of blades for opening sheath

/ Associated products

	Reference	Designation
	CWB/18-60-FEP	Tool to remove bonded semiconductor with chamfer on the semiconductor cutback
	BRMRD1E	Insulation remover 14 - 40 mm