



See online
technical sheet

/ LW03-05 Sectional clampstick



/ Standards

- CEI 60855-1
- ASTM F711
- IEC 60832-1
- ASTM F1825

/ Use

The sectional clampstick is the most universal tool used to install and remove personal protective grounding clamps, to install plastic and rubber cover-up equipment, etc. Pole diameter 32mm (1 1/4") and operating rod 10mm (2/5").

Ideal for workers with limited storage space in their vehicles. The device is lightweight, interlocking and very robust.

The length of the pole is defined by the operating handle and ensures a good grip on the pole.

Insulating tube, fiberglass over the foam core. Control rod is also made of insulating material.



Hook and mechanism made of corrosion-resistant metal.

High-performance plastic pole head with integrated and replaceable hook.

/ Advantages

- Easily adjustable length
- A solution for all tensions
- Varnish finish
- Insulating quick-release fittings





/ Areas of activity

-  Electrical distribution
-  Transport

/ Technical specifications

- Pole kind : Extendable
- Work type : Live working
- Part number : 3
- Pipe diameter (mm) : 32
- Operating voltage (V) : HTA, HTB
- Pole finition (terminal element) : Polish
- Press button
- Pipe kind : Rounded
- Color : Red
- Rod diameter (mm) : 10
- Rod diameter (inch) : 2/3"
- Pipe diameter (inch) : 1" 1/4

/ Associated products

	Reference	Designation
	LW11-01	Universal adapter for clampstick
	LW14-10	Stick hanger
	LW14-05	Product cleaning
	TC53	Insulated silicone-coated cloth

/ Table legend

* Insulating length = part between the tool head and the hand positioning guard, ensuring operator insulation.

Product reference	Total length (m)	Insulating length (m)	Pole weight (kg)	Total length (inch)	Insulating length (inch)	Spare part	Pole weight (pounds)
LW03-05-32-HA-11	2.00	0.70	1.7	3'7"	3"	Flagpole	3.7
LW03-05-32-HA-35	3.50	1.15	3.3	11'5"	7'2"	Flagpole	7.3
LW03-05-32-RA-12	1.20	1.10	1.2	3'11"	3'7"	Pole extension	2.6
LW03-05-32-RA-18	1.80	1.70	1.7	5'10"	5'6"	Pole extension	3.7
LW03-05-32-RA-24	2.40	2.30	2.1	7'10"	7'6"	Pole extension	4.6
LW03-05-32-RA-30	3.00	2.90	2.6	9'10"	9'6"	Pole extension	5.7
LW03-05-32-ET-06	0.60	0.50	0.9	1'11"	1'7"	End element	2.0