



See online
technical sheet

/ LW04-01

Conductor support stick



/ Standards

- CEI 60855-1
- ASTM F711
- IEC 60832-1

/ Use

The conductor support stick is used to grip a conductor or other accessories in order to hold them in a certain position or to move them when necessary.

It is commonly used in combined applications, such as triangulation or mast assemblies, and is referred to as a support pole or spacer pole, depending on its function.

Insulating tubes, fiberglass over the foam core.

Clamp and swivel ring, made of corrosion resistant metal.

/ Advantages

- Stronger
- Tool validated at 2.5x CMU
- Varnish finish
- High mechanical strength

/ Areas of activity

-  Electrical distribution
-  Transport

/ Technical specifications

- Pole kind : Fixed
- Work type : Live working
- Pipe kind : Rounded
- Color : Red
- Clamping capacity (mm) : 4 à 50
- Clamping capacity (Inch) : 1/6" - 2"



Product reference	Operating voltage (V)	Pole weight (kg)	Pole weight (pounds)	Pipe diameter (mm)	Pipe diameter (inch)	Total length (m)	Total length (inch)	Longueur isolante (m)	Insulating length (inch)
LW04-01A-39-270	HTA (1 000 V to 50 000 V)	3.5	7.7	39	1"1/2	2.70	8'10"	2.40	7'10"
LW04-01B-39-270	HTB (> 50 000 V)	3.5	7.7	39	1"1/2	2.70	8'10"	2.40	7'10"
LW04-01A-39-330	HTA (1 000 V to 50 000 V)	4.3	9.5	39	1"1/2	3.30	10'9"	3.00	9'10"
LW04-01B-39-330	HTB (> 50 000 V)	4.3	9.5	39	1"1/2	3.30	10'9"	3.00	9'10"
LW04-01A-64-390	HTA (1 000 V to 50 000 V)	9.3	20.5	64	2"1/2	3.90	12'9"	3.60	11'9"
LW04-01B-64-390	HTB (> 50 000 V)	9.3	20.5	64	2"1/2	3.90	12'9"	3.60	11'9"
LW04-01A-64-465	HTA (1 000 V to 50 000 V)	11.6	25.6	64	2"1/2	4.65	15'3"	4.35	14'3"
LW04-01B-64-465	HTB (> 50 000 V)	11.6	25.6	64	2"1/2	4.65	15'3"	4.35	14'3"
LW04-01A-64-510	HTA (1 000 V to 50 000 V)	13.5	29.8	64	2"1/2	5.10	16'8"	4.50	14'9"
LW04-01B-64-510	HTB (> 50 000 V)	13.5	29.8	64	2"1/2	5.10	16'8"	4.50	14'9"