

/ EMP-07886 PB50F Ferrule Terminal



See online
technical sheet



/ Standards

- ENA-41-21

/ Use

For use upon Field Equipment Earth.
Suitable for 50sqmm Aluflex cable. For fitting to CE10/A2, CE13/A, CE69, and CE81 Clamps.

Earth bonds are of a 120 sqmm nominal section terminated either by PB120 palm type terminations or PB120F Ferrule terminations, depending upon which style CE60 Sparrow plate is used. Flexible clear P.V.C. Stress-relieving sleeves are fitted to prevent excessive wear around the compression joints.







/ Areas of activity



/ Technical specifications

- Product specificity : Permanent
- Product kind : Cable
- Composition : Aluminium
- Cross-section (mm²) : 50
- Marking : PB50F
- Weight (kg) : 0.03kg
- Compatible Cable : 50sqmm Aluflex Leads
- Strain Relief Type : 50sqmm Stress Relief Sleeve (6112-01)

/ Associated products

	Reference	Designation
	EFP-16710	CE60 Sparrow Plate MK2 (POST-2014)
	EFP-16785	CE60 Sparrow Plate MK1 (PRE-2014)
	EFP-11173/1	CE10/A2 Earth End Clamp
	EFP-11868	CE13 Line End Clamp
	EFP-16743	CE69 Line End Clamp
	EFP-16790	CE81 Line End Clamp