



See online
technical sheet

/ GS16

Single open ended spanner ATEX II



/ Standards

NF E 74400 / ISO 691 / ISO 1711-1 / ISO 3318 / ISO 10102

/ Technical specifications

The thickness of the head is the lowest existing on the market.
Other dimensions available on request.

Product reference	Weight (g)	Description	Ouverture (mm)
GS16 10	40	Clé à fourche 1 tête 10 mm Atex II	10
GS16 11	40	Clé à fourche 1 tête 11 mm Atex II	11
GS16 13	50	Clé à fourche 1 tête 13 mm Atex II	13
GS16 14	70	Clé à fourche 1 tête 14 mm Atex II	14
GS16 17	100	Clé à fourche 1 tête 17 mm Atex II	17
GS16 19	140	Clé à fourche 1 tête 19 mm Atex II	19
GS16 21	200	Clé à fourche 1 tête 21 mm Atex II	21
GS16 22	180	Clé à fourche 1 tête 22 mm Atex II	22
GS16 23	220	Clé à fourche 1 tête 23 mm Atex II	23
GS16 24	210	Clé à fourche 1 tête 24 mm Atex II	24
GS16 27	260	Clé à fourche 1 tête 27 mm Atex II	27
GS16 30	370	Clé à fourche 1 tête 30 mm Atex II	30
GS16 32	370	Clé à fourche 1 tête 32 mm Atex II	32
GS16 36	580	Clé à fourche 1 tête 36 mm Atex II	36