



See online  
technical sheet

## / E08

Dry powder fire extinguishers on wheels



## / Standards

EN 1866-1:2008 Directive 96/98/EC (MED)

## / Use

Wheeled extinguisher designed for professional use under severe circumstances, resulting in a high level of quality and ease of use.

Fire classes : A - IVB - C

## / Technical specifications

Wheeled extinguisher designed for professional use under severe circumstances, resulting in a high level of quality and ease of use.

- Headcap 2" BSP : the headcap is made of brass and equipped with a spring loaded safety valve
- Propellant bottle : N2 nitrogen bottle, chrome molybdenum steel
- Extinguishing agent : dry chemical powder, it is non-corrosive, non-abrasive, and is non toxic for humans and animals
- Discharge device : equipped with a highly flexible hose 5 m long made of EPDM rubber with an excellent resistance. The specially designed patented pistol ensures a steady flow of powder with a very low drop in pressure.
- Ease of mobility : large wheels with rubber tires and push bar ensures good stability during operation.

Discharge time : 25 sec for 25 kg model and 41 sec for 50 kg model

Jet length : 11 m

Operating temperature range : -30°C +60°C

Fire classes : A - IVB - C

## Advantages

Very mobile and easy to operate.  
Extremely high ratings on A, B and C class fires.  
Can be used at low temperatures (-30°C)

Product reference	Dimensions (mm) - 11019	Description	Weight charged (kg) - 11402	Capacity (kg)	Weight charged (kg)	Capacity (kg) - 10875
E08 25KG	1020 x 430 x 535	Extincteur à poudre 25 kg sur roues	60	-	-	25
E08 50KG	1050 x 450 x 535	Extincteur à poudre 50 kg sur roues	-	50	84	-