

/ RTTE25 Insulating Pole



See online
technical sheet



/ Standards

- EN 50508
- CEI 60855-1
- ASTM F711

/ Use

Insulated pole for performing voltage absence verification (VAT) operations. This equipment is designed for the safe lockout of all networks, whether AC or DC.

Lightweight, portable, and extremely robust. Can be used in a wide range of temperatures (-25 to 55°C) and indoors or outdoors.

The length of the shaft, defined by a hand guard, ensures a good grip on the pole.

RTTE insulating pole in 1 section for low voltages up to 36kV.

2 skirts per section (excluding shaft and RTTE63 terminal element)

Physical hand guard

Shaft with grip sleeve

Enveloping cap at the lower end




Extensions:

RE115: 1.5 m, 1.2 kg

RE165: 1.65 m, 1.65 kg

RE215: 2.15 m, 2 kg

/ Areas of activity

-  Electrical distribution
-  Industry
-  Substation

/ Technical specifications

- Pole kind : Extendable
- Pipe diameter (mm) : 39
- Pole finition (terminal element) : Polish
- pole-finition-inferior : Polish
- Pipe kind : Rounded
- Pole weight (kg) : 1.3
- Pole material : Composite foam glass fiber
- Telescopic pole material : Composite foam glass fiber

- Total length (m) : 1.6
- Insulating length (m) : 0.95
- Cover reference : H10

