



See online technical sheet

/ CPUNITAGU

Phase tester for LV network



/ Standards

1000V CAT IV - IP65

/ Use

UNITAG is a unipolar detector designed to test the presence of phase on insulated or bare LV conductors. The level of detection is indicated by a LED bargraph and a beeping sound which speed increases as device approaches a live source.

It is commonly used for detecting stray voltage on poles and cross arms, conductor disconnection on overhead insulated LV conductors....

UNITAG will not replace a standard "proving dead" device but is an ideal complement to bipolar LV detector.

/ Technical specifications

- AC system
- AC mains frequency : 50-60 Hz
- Field of use : from 50V up to 1000V
- Detection by direct contact at 50V
- CAT IV 1000V
- IP65
- Temperature : - 15 ° C to +45 ° C
- 2 x LR03 1.5 volt alkaline (AAA)
- Delivered with soft bag suitable for belt fixing

Advantages

- Sound and light alert on voltage presence.
- UNITAG 1000V for using on networks.
- Can be used by hands or on insulating stick.
- Indication of detection level.
- Tip length designed for access to LV panel and test point.
- Audible beeping speed proportional to the level of detection.
- Visual indication of level of detection on a bright LED bar graph.
- Automatic self-test when switched on with green LED indication.
- Multi purpose detector : street light, insulating twisted cables, rescue team, fire fighters...