/ TAG200BC

Voltage Detector for voltage capacitive test points TAG200BC

See online technical sheet



/ Standards

- Complies with EDF-SPS technical specification n° 42
- CE compliante

/ Use

electrical-detection / TAG200BC / penta-catchprase-complement

• TAG200BC is designed to check presence or absence of nominal voltage on the voltage capacitive test points of elbows and cable terminals defined in standard NF C 33-051 of electrical installations with a nominal voltage between 3 kV and 36 kV.

• Its insulated and elbowed electrode allow removing, handling and re-placement the insulating caps on voltage capacitive test points.

• The elbow electrode has an "universal" end fitting for fixing and handling the detector at the end of an insulating stick adapted to the nominal voltage of the installation to be tested.

/ Advantages

- penta-pim-advantage-voltage/validation-of-autotest-and-watch-state-by-a-green-sight
- The presence of voltage within the calibrated range or above is indicated by a RED light and a beeping sound
- The self test checks all the circuits, the reference detection level and the battery voltage

/ Areas of activity

- Electrical distribution
- Electric traction
- Industry
- Substation

Document not contractually binding, errors and omissions excepted

/ Technical specifications

- **Power type :** AC Voltage
- **Packaging :** Soft case with conductive lining for EMC protection
- **Network frequency (Hz) :** 50/60
- **Use condition :** Indoor, Outdoor
- **Hymidity (Max) (%) :** 96
- **Battery type :** 9V battery (x1)
- **End fitting :** Universal (U)
- **Electrode type (mm) :** Angled
- **Case material :** Polycarbonate
- **Color :** Yellow
- **Dimensions (mm) :** 275 x 56 x 56
- **Weight (kg) :** 0,45
- **Temperature of use (C°) :** -20...+50
- **Type of indication :** Acoustic indication, Indicator lights
- **Operating voltage (V) :** HTA







Document not contractually binding, errors and omissions excepted

/ Table legend

electrical-detection / TAG200BC 🗂 / penta-table-legend

Product reference	Voltage range
200BC	10-30
200BC0615H	6-15
200BC1036H	10-36
200BC0310H	3-10
200BC0336H	3-36
200BC0520H	5-20
200BC0636H	6-36

Document not contractually binding, errors and omissions excepted