



See online
technical sheet

/ PG3HTA SERIE








/ Use

PG3HTA pliers enable the user to make a circular and longitudinal cut in order to remove the outer sheath of the cable. All cutting depths are available on demand from 0.5 to 5mm.

/ Advantages

- Robust design
- Fast deployment
- Easy to get to grips with
- Faster and safer than a knife
- Cutting depth control

/ Areas of activity




- | | |
|--|--|
|  Cable & Connections |  Production |
|  Electrical distribution |  Substation |
|  Industry | |

/ Technical specifications




- **Specific tools :** Cable tools
- **Cable tools :** Cable tools
- **Areas of activity :** Cable & Connections, Electrical distribution, Industry, Production, Substation
- **For network cables :** medium voltage
- **Packaging :** Carton box
- **Weight (g) :** 600
- **Lenght (mm) :** 265
- **Width (mm) :** 95

- **Height (mm) :** 80
- **Max diameter (mm) :** 52
- **Mini diameter (mm) :** 26
- **Tools king :** Specific tools

/ Spare parts

	Reference	Designation
	MTC3/**	Circular cutting wheel
	LGPG	Set of blades for opening sheath
	MTL3/**	Longitudinal cutting wheel

/ Associated products

	Reference	Designation
	CWB/18-60-S	Bonded semiconductor removal tool complete with chamfer cut and Auto-Stop function
	MF2/40	Multifunction tool for outer sheath and insulation
	MF1+/25	Tool for bonded semiconductor

Product reference	Circular cutting depth	Longitudinal cutting depth
PG3HTA/2020	2 mm	2 mm
PG3HTA/2530	2.5 mm	3.0 mm
PG3HTA/2828	2.8 mm	2.8 mm
PG3HTA/2833	2.8 mm	3.3 mm
PG3HTA/3035	3 mm	3.5 mm