



See online technical sheet

/ ARCBLOUSE11-B-BR

Arc Flash coat with retroreflective tapes, APC 1, ATPV 11 cal/cm², ELIM 9.1 cal/cm²



/ Standards

- EN ISO 11612:2015 (Flamme and heat) : A1, A2, B1, C1, E3, F1
- EN ISO 11611:2015 (Welding protection) : Class 1
- EN1149 (Electrostatic property) : EN1149-5
- IEC 61482-2
- CE category : Catégory 3

/ Use

For occasional use. For chemical industries, electrical industries, refineries.
Resistant to electrostatic charges, flame, heat and molten metal splashes.
Resistant to liquid chemical splashes and thermal hazards of an electric arc.

/ Advantages

- Modern, ergonomic design
- ATEX zone: for use in explosive atmospheres
- Dual certification using 2 test methods: BOX TEST & OPEN ARC
- Double qualification according to ATPV and ELIM for OPEN ARC
- No metal parts (non-magnetic)
- Can be customised by non-flame transfer (please consult us)

/ Areas of activity

-  Industry
-  Electric mobility

/ Technical specifications

- **Main color** : Dark blue
- **Size** : S, M, L, XL, 2XL, 3XL
- **Workwear color** : Dark blue
- **Fastening** : Snap fastener
- **Top Reflective piping** : Arm
- **Collar style** : Low blas collar
- **Cloth composition table** : Composition - 64% cotton 35% polyester 1% antistatic fiber - 350 g/m² | 4x Pocket

