



See online
technical sheet

/ E07 2KGS

Carbon dioxide (CO₂) fire extinguisher, capacity 2 kg



/ Standards

Certified to the Pressure Equipment Directive PED 97/23/EC, Marine Equipment Directive MED 96/98/EC and CEN EN3

/ Use

Suitable for class B fires - Flammable liquids.
Fire class : B34

/ Technical specifications

Carbon dioxide (CO₂) fire extinguisher with lever valve and front horn :

- Body : Single piece steel body, externally painted with polyester resin, signal red RAL 3000.
- Valve : The valve is lever operated with nickel brass body. Front -outlet type, provided with burst disk safety relief valve. All external valve parts are protected against corrosion.
- Extinguishing agent : Carbon dioxide (CO₂). All parts in contact with the extinguishing agent are compatible with the same.
- Horn : Front horn in polyamide.
- Bracket : Mild steel, zinc plated wall bracket suitable for vertical mounting.

Operating temperature : -30°C +60°C

Fire class : B34

Product reference	Capacité (kg)	Description	Poids chargé (kg)	Capacity (kg)	Weight charged (kg)	Spécificité
E07 2KGS	2	Extincteur à dioxyde de carbone (CO ²) capacité 2 kg	5	-	-	Avec étiquette S1130
E07SEUL2KG	-	Extincteur dioxyde de carbone capacité 2 kg	-	2	5	Sans étiquette