



See online
technical sheet

/ Cosses C Bypass fitting



/ Use

The C terminal or grounding conductor branch connector allows two grounding cables to be crossed or branched without interrupting either the main cable or the grounding conductor.

/ Technical specifications

- Product specificity : Permanent
- Product kind : Accessories
- Field of use (environment) :
- Station office : After electric meter
- After electric meter : Industria
- Short-circuit intensity $kA/0.5s$: 63
- Short-circuit intensity $kA/1s$: 30 à 40
- Accessory materials : Copper

/ Table legend

Application is by crimping, and requires special tooling comprising crimping pliers and associated dies.

Product reference	Composition	Weight (kg)	Measurement
C95E	RDCT-75/75 : Cosse C pour deux câbles de 75mm ²	0,14	-
C120E	RDCT-116/75 et RDCT-116/116 : Cosse C pour deux câble de 70-75mm ² et 120mm ² ou deux câbles de 120mm ²	0,16	-
C150E	RDCT-146/75 et RDCT-146/146 : Cosse C pour deux câbles de 70-75mm ² et 150mm ² ou deux câbles de 150mm ²	0,12	45x30x28mm
C185-95E	RDCT-182/75 : Cosse C pour deux câbles de 70-75mm ² et 185mm ²	0,13	-
C185E	RDCT-182/182 : Cosse C pour deux câbles de 185mm ²	0,25	-