




See online  
technical sheet

## / MF3/40-SSR

Multifunction tool for outer sheath and insulation



## / Use

The MF3/40-SSR tools enables the user to :





Remove the outer sheath (PE-PVC-PR) with a straight and neat cut

Set the length to be removed and remove the insulation with a straight and neat cut

## / Advantages

- Smooth finish
- Robust design
- Easy to get to grips with
- Adjustment of the tool feed (chip thickness)
- 3 in 1 tools : sheath - peelable semicon - insulation
- Clean stop of the sheath and the insulation
- Precise control of the incision of the peelable semiconductor

## / Areas of activity


- |  |  |
|--|--|
|  Cable & Connections     |  Substation |
|  Electrical distribution |  |
|  Industry                |  |

## / Technical specifications




- **Specific tools :** Cable tools
- **Cable tools :** Cable tools
- **Areas of activity :** Cable & Connections, Electrical distribution, Industry, Substation
- **For network cables :** medium voltage
- **Packaging :** Carton box
- **Weight (kg) :** 1,38
- **Lenght (mm) :** 305
- **Width (mm) :** 100

- **Height (mm) :** 165
- **Section (mm<sup>2</sup>) :** 25 à 240
- **Max diameter (mm) :** 40
- **Mini diameter (mm) :** 16
- **Limit stop :** None
- **Stylet inclus :** None
- **Remining length of semi conductor (MIN) (mm) :** 30
- **Incision depth on semi-peelable material :** En option

## / Spare parts

	Reference	Designation
	LMF2	Blade for outer sheath and primary insulation

## / Associated products

	Reference	Designation
	DSP	Peelable semiconductor lifter
	ALROC-FENTE	Splitter for outer sheath 50-630 mm <sup>2</sup>
	ROTO-TMG	Maintaining tool for mechanical fitting connectors