

## / MF3/60-C


Multifunction tool for outer sheath, peelable semiconductor and insulation



See online technical sheet

## / Standards

- ENEDIS



## / Use

The MF3/60-C tool enables the user to :

Remove the outer sheath (PE-PVC-PR) with a straight and neat cut





Score the peelable semiconductor with a chamfer on the edge of the semiconductor cutback (with the SRC scoring stylus delivered with the tool)

Set the length to be removed and remove the insulation with a straight and neat cut

## / Advantages

- Smooth finish
- Heavy duty
- Easy to get to grips with

## / Areas of activity

-  Cable & Connections
-  Substation
-  Electrical distribution
-  Industry

## / Technical specifications

- **Specific tools** : Cable tools
- **Cable tools** : Cable tools
- **Operating voltage (V)** : HTA (1 000 V to 50 000 V)
- **Packaging** : Carton box
- **Weight (kg)** : 1.75
- **Length (mm)** : 305
- **Width (mm)** : 115
- **Height (mm)** : 165
- **Max diameter (mm)** : 58
- **Mini diameter (mm)** : 16
- **Limit stop** : None
- **Stylet inclus** : SRC
- **Remining length of semi conductor (MIN) (mm)** : 30
- **Profondeur d'incision sur semi pelable** : 0,4 / 0,7 / 0,9 / 1,1
- **Scoring depth MAX (mm)** : 1.5
- **Cutting depth (max) on insulation** : 7