




See online
technical sheet

/ MF3/45-C

Multifunction tool for outer sheath, peelable semiconductor with chamfer and insulation



/ Standards

- ENEDIS

/ Use

The MF3/45-C tools enables the user to :

Remove the outer sheath (PE-PVC-PR) with a straight and neat cut





Score the peelable semiconductor with a chamfer on the edge of the semiconductor cutback (with the SRC scoring stylus delivered with the tool)

Set the length to be removed and remove the insulation with a straight and neat cut

/ Advantages

- Robust design
- Adjustment of the tool feed (chip thickness)
- 3 in 1 tools : sheath - peelable semicon - insulation
- Clean stop of the sheath and the insulation
- Precise control of the incision of the peelable semiconductor



/ Areas of activity

-  Cable & Connections
-  Substation
-  Electrical distribution
-  Industry

/ Technical specifications

- **Specific tools :** Cable tools
- **Cable tools :** Cable tools
- **Areas of activity :** Cable & Connections, Electrical distribution, Industry, Substation
- **For network cables :** HTA
- **Packaging :** Carton box
- **Lenght (mm) :** 303
- **Width (mm) :** 95
- **Height (mm) :** 165
- **Weight (kg) :** 1,5
- **Max diameter (mm) :** 45
- **Mini diameter (mm) :** 16
- **Cut deepness (mm) :** 7
- **Limit stop :** None
- **Scoring depth MAX (mm) :** 1.5

/ Spare parts

	Reference	Designation
	LMF2	Blade for outer sheath and primary insulation
	LS-C	Blade for peelable semi-conductor