




See online
technical sheet

/ MF2/40 SERIE

Multifunction tool for outer sheath and insulation

/ Standards

- ENEDIS







/ Use

The MF2/40 enables the user to :
Remove the outer sheath (PE-PVC-PR) with a straight and neat cut
Set the length and remove thicker insulation with a straight and neat cut

/ Advantages

- Robust design
- Adjustment of the tool feed (chip thickness)
- Clean stop of the sheath and the insulation
- Outils 2 en 1 : Gaine - Isolant

/ Areas of activity


-  Cable & Connections
-  Substation
-  Electrical distribution
-  Industry

/ Technical specifications



- **Specific tools** : Cable tools
- **Cable tools** : Cable tools
- **Areas of activity** : Cable & Connections, Electrical distribution, Industry, Substation
- **For network cables** : HTA
- **Packaging** : Carton box
- **Max diameter (mm)** : 40
- **Mini diameter (mm)** : 16
- **Tools king** : Specific tools

- **Product universe** : Work
- **Penta marque** : PENTA ESP

/ Spare parts

	Reference	Designation
	LMF2 SERIE	Insulation and sheath blades

/ Associated products

	Reference	Designation
	SRC	Adjustable scoring stylus for peelable semiconductor with chamfered transition
	MF1+/25	Tool for bonded semiconductor

Product reference	Cut deepness
MF2/40	7 mm
MF2/40-S	11 mm