


/ PCT SERIE

Triple protections



See online
technical sheet



/ Use

Triple protections allow three cables to be held and protected. They are compulsory for the proper installation of cleats.

Their shape has been designed especially to make closing easier and to limit the sliding of the cable as much as possible.

They are precut to the size of each cleat and slide inside the cleat before it is closed.

/ Advantages

- High vertical slip resistance
- Protective cable liner

/ Technical specifications

- Collar type : Aluminium
- Tools king : Specific tools
- Cable configuration : Triple
- Material : EPDM

/ Associated products

	Reference	Designation
	CST E SERIE	Triple aluminium cleats
	CST V SERIE	Triple aluminium cleats

Product reference	Cleat diameter	Cable diameter
PCT 10-60	60 mm	42 - 44 mm
PCT 8-60	60 mm	44 - 47 mm
PCT 10-65	65 mm	47 - 49 mm
PCT 8-65	65 mm	49 - 52 mm
PCT 8-70	70 mm	52 - 54 mm
PCT 10-70	70 mm	54 - 57 mm
PCT 10-75	75 mm	57 - 59 mm
PCT 8-75	75 mm	59 - 62 mm
PCT 10-80	80 mm	62 - 64 mm
PCT 10-85	85 mm	69 - 72 mm
PCT 8-80	80 mm	64 - 67 mm
PCT 8-85	85 mm	67 - 69 mm