



See online
technical sheet

/ EMP-07897

PB95F Ferrule Termination



/ Standards

- ENA-41-21

/ Use

Our terminations are manufactured from specially milled and certified material and precision machined in our works, tested rigorously throughout the manufacturing process to ensure quality and performance.

For use upon Field Equipment Earth.

Suitable for 95sqmm Aluflex cables with 150sqmm Tension Spring.

/ Advantages

- Lightweight
- Single bit compression
- Sheath encapsulated within termination

/ Areas of activity



Transport

/ Technical specifications

- Product specificity : Permanent
- Product kind : Cable
- Composition : Aluminium
- Cross-section (mm²) : 95
- Marking : PB95F
- Weight (kg) : 0.13kg
- Compatible Cable : 95sqmm Aluflex Leads
- Strain Relief Type : 150sqmm Tension Spring (EBP-14714)

/ Accessories

	Reference	Designation
	EBP-14714	150sqmm Tension Spring

/ Products contained in the kit

	Reference	Designation
	EBL-19108	95sqmm Clear Aluflex Lead

/ Associated products

	Reference	Designation
	EMP-07889	PB95T Alu. Termination with ø13 Hole
	EMP-07889/1	PB95T Alu. Termination with ø11 Hole
	EMP-07889/2	Alu. Termination with ø13 Hole Long Palm
	EBL-19108	95sqmm Clear Aluflex Lead