




See online
technical sheet

/ CORATRIF

Complete earthing and short-circuiting device







/ Standards

- CEI 61230

/ Advantages

- High clamping capacity
- Fast and easy to use






/ Areas of activity

-  Electrical distribution
-  Industry
-  Civil security
-  Transport

/ Technical specifications

- Product kind : Earthing equipment/kits
- Clamp material : Cupro-alu
- Clamp tightening (mm) : Rond : Ø7 à 37mm, Plat : jusqu'à 37mm, Boule : Ø20 et 25mm
- Conductor type : Ball, Round, Flat
- Type of trifurcation : T = Trifurcation with PVC coating
- Operating voltage (V) : HTA
- Phase cable number : 3
- Phase(s) cable cross-section (mm²) : 70
- Phase(s) cable length (m) : 1,5
- Cross-section (mm²) : 35
- Floor cable length (m) : 2
- Short-circuit intensity kA/1s : 18,5
- Phase câble
- Measurement : 910x240x105mm
- Weight (kg) : 15
- Floor cable

/ Products contained in the kit

	Reference	Designation
	CM535	Empty metal box for earthing device
	T70015C35020C	Set of cables for short-circuiting and earthing devices
	NBD25M	Earthing clamp for fixed ball points
	NBD25AP	Earthing clamp for fixed ball points
	TR245	TR245