

/ E25 Roundslings



See online
technical sheet



Model	Length (m)	Width (mm)	Weight (kg)	Max. Load (kg)	Material
E25	1.5	25	1.5	3000	Polyester
E25	2.0	25	2.0	3000	Polyester
E25	2.5	25	2.5	3000	Polyester
E25	3.0	25	3.0	3000	Polyester
E25	3.5	25	3.5	3000	Polyester
E25	4.0	25	4.0	3000	Polyester
E25	4.5	25	4.5	3000	Polyester
E25	5.0	25	5.0	3000	Polyester
E25	5.5	25	5.5	3000	Polyester
E25	6.0	25	6.0	3000	Polyester
E25	6.5	25	6.5	3000	Polyester
E25	7.0	25	7.0	3000	Polyester
E25	7.5	25	7.5	3000	Polyester
E25	8.0	25	8.0	3000	Polyester
E25	8.5	25	8.5	3000	Polyester
E25	9.0	25	9.0	3000	Polyester
E25	9.5	25	9.5	3000	Polyester
E25	10.0	25	10.0	3000	Polyester

/ Standards

EC marking / EN 1492-2

/ Technical specifications

Highly resistant 100% parallel polyester fibres in anti-abrasion-treated sheath.

Level of resistance equal to that of steel, but lighter, more flexible, easier to handle, and compliant with safety requirement. Low elongation.

Totally rot-proof and chemical proof.

Each type of roundslings is identified by a different colour. Roundslings also bear a label indicating the maximum vertical static load (CMU) and the materials used.

If requested, it is possible to adapt 1 PVC sleeve with a sheath stitched onto a loop. (factory operation)

Safety factor 7:1