



See online
technical sheet

/ BLC25

Battery operated hydraulic cable cutter Ø 25 mm

| | TYPE DE CÂBLES | DURÉE MAX. | Ø MAXI. DE COUPE * |
|---------------------|-------------------------|-------------------------------|--------------------|
| CÂBLES MULTI-TORONS | 7 x 19 torons - acier | 150 > 160 daN/mm ² | Ø 10 > 16 mm |
| | 7 x 37 torons - acier | 150 > 160 daN/mm ² | Ø 12 > 18 mm |
| CÂBLES ÉLECTRIQUES | Alu - aluminium | | Ø 20 |
| | Alu - aluminium - acier | | Ø 20 > 22 mm |
| BÂTTES CYLINDRIQUES | Alu - aluminium | | Ø 10 > 12 mm |
| | Alu - aluminium - acier | | Ø 10 > 12 mm |
| | Alu - aluminium | | Ø 10 > 12 mm |
| | Alu - aluminium | | Ø 10 > 12 mm |
| | Alu - aluminium | | Ø 10 > 12 mm |
| CÂBLES ISOLÉS | Alu - aluminium | | Ø 10 > 12 mm |
| | Alu - aluminium | | Ø 10 > 12 mm |

* Autres dimensions et câbles à valider sur essais.

/ Technical specifications

- Tools king : Specific tools

