



See online  
technical sheet

## / BC40

Battery operated hydraulic cable cutter Ø 40 mm

	TYPE DE CÂBLES	DURETÉ MAXI.	Ø MAXI. DE COUPE (mm) *
CÂBLES	Cuivre	< 60 daN/mm <sup>2</sup>	Ø 32 (Ø 30 mm)
	Aluminium	< 50 daN/mm <sup>2</sup>	Ø 40
	Alu-mag.	< 34 daN/mm <sup>2</sup>	Ø 40
	Acier	< 180 daN/mm <sup>2</sup>	7 x Ø 2,5 (x Ø 2,0)
			19 x Ø 2,1 (x Ø 1,5)
			19 x Ø 2,2 (x Ø 1,5)
	Multi-brins acier	< 180 daN/mm <sup>2</sup>	Ø 18 (garantie de force : 200)
	ACSR	< 180 daN/mm <sup>2</sup>	35 x Ø 2,52 x 7 x Ø 1,95 (x Ø 1,85)
	(câble aluminium renforcé acier)		35 x Ø 2,52 x 7 x Ø 2,25 (x Ø 1,95)
			35 x Ø 2,60 x 7 x Ø 2,80 (x Ø 2,25)
BÂBES	Acier	< 60 daN/mm <sup>2</sup>	34 x Ø 2,50 x 19 x Ø 2,10 (x Ø 2,00)
			Ø 18
	Cuivre	< 60 daN/mm <sup>2</sup>	Ø 35
	Aluminium	< 50 daN/mm <sup>2</sup>	Ø 35
	Aluminium	< 25 daN/mm <sup>2</sup>	Ø 32
		< 16 daN/mm <sup>2</sup>	Ø 40

\* Autres dimensions et câbles à valider sur essais.

## / Technical specifications

- Tools king : Specific tools

