




See online
technical sheet

/ MF3/40-C

Multifunction tool for outer sheath, peelable semiconductor and insulation

/ Standards

- ENEDIS



/ Use

The MF3/40-C tool enables the user to :

Remove the outer sheath (PE-PVC-PR) with a straight and neat cut

Score the peelable semiconductor with a chamfer on the edge of the semiconductor cutback (with the SRC scoring stylus delivered with the tool)

Set the length to be removed and remove the insulation with a straight and neat cut

/ Advantages

- Smooth finish
- Robust design
- Easy to get to grips with
- Adjustment of the tool feed (chip thickness)
- 3 in 1 tools : sheath - peelable semicon - insulation
- Clean stop of the sheath and the insulation
- Precise control of the incision of the peelable semiconductor

/ Areas of activity



Cable & Connections



Substation



Electrical distribution





Industry

/ Technical specifications




- **Specific tools :** Cable tools
- **Cable tools :** Cable tools
- **Areas of activity :** Cable & Connections, Electrical distribution, Industry, Substation
- **For network cables :** medium voltage
- **Packaging :** Carton box
- **Weight (kg) :** 1,46
- **Lenght (mm) :** 305
- **Width (mm) :** 100

- **Height (mm) :** 165
- **Section (mm²) :** 25 à 240
- **Max diameter (mm) :** 40
- **Mini diameter (mm) :** 16
- **Limit stop :** None
- **Stylet inclus :** SRC
- **Remining length of semi conductor (MIN) (mm) :** 30
- **Incision depth on semi-peelable material :** 0,4 - 1,5

/ Spare parts

	Reference	Designation
	LMF2	Blade for outer sheath and primary insulation
	LS-C	Blade for peelable semi-conductor

/ Associated products

	Reference	Designation
	DSP	Peelable semiconductor lifter
	ALROC-FENTE	Splitter for outer sheath 50-630 mm ²
	ROTO-TMG	Maintaining tool for mechanical fitting connectors