



Ver la ficha técnica
en línea

/ MS86

Vaso 12 caras hembra aislado 3/8"



/ Normas

EN 60900 / CEI 60900 / ISO 691 / ISO 1174-1 / ISO 1711-1 / ISO 2725-1

/ Uso

Manual sockets suitable for use with standard or mechanically locking ratchets.

/ Características

Chrome vanadium steel.

Socket with 4 ogive-type recesses inside the female square to accommodate the crimped ball of the ratchet and thus ensure a safe and effective holding of the assembly (up to 500 Newtons to the pull-out).

A flange is included for optimum electrical protection when used with a ratchet spanner or an extension.

/ Table legend

Other dimensions available on request (metric, inch, Withworth, BA).

Ventajas

- Outer diameter reduced to a minimum for optimum accessibility on installations.
- The 12-sided profile preserves screws and nuts.

| Product reference | Diámetro | Peso (g) | Désignation |
|-------------------|----------|----------|--|
| MS86 08 | 8 mm | 35 | Douille femelle isolée 3/8" 12 pans 8 mm |
| MS86 09 | 9 mm | 35 | Douille femelle isolée 3/8" 12 pans 9 mm |
| MS86 1/2 | 1/2" | 45 | Douille femelle isolée 3/8" 12 pans 1/2" |
| MS86 10 | 10 mm | 40 | Douille femelle isolée 3/8" 12 pans 10 mm |
| MS86 11 | 11 mm | 40 | Douille femelle isolée 3/8" 12 pans 11 mm |
| MS86 11/16 | 11/16" | 50 | Douille femelle isolée 3/8" 12 pans 11/16" |
| MS86 12 | 12 mm | 40 | Douille femelle isolée 3/8" 12 pans 12 mm |
| MS86 13 | 13 mm | 45 | Douille femelle isolée 3/8" 12 pans 13 mm |
| MS86 13/16 | 13/16" | 110 | Douille femelle isolée 3/8" 12 pans 13/16" |

| Product reference | Diámetro | Peso (g) | Désignation |
|-------------------|----------|----------|---|
| MS86 14 | 14 mm | 45 | Douille femelle isolée 3/8" 12 pans 14 mm |
| MS86 15 | 15 mm | 45 | Douille femelle isolée 3/8" 12 pans 15 mm |
| MS86 16 | 16 mm | 50 | Douille femelle isolée 3/8" 12 pans 16 mm |
| MS86 17 | 17 mm | 50 | Douille femelle isolée 3/8" 12 pans 17 mm |
| MS86 18 | 18 mm | 70 | Douille femelle isolée 3/8" 12 pans 18 mm |
| MS86 19 | 19 mm | 70 | Douille femelle isolée 3/8" 12 pans 19 mm |
| MS86 20 | 20 mm | 80 | Douille femelle isolée 3/8" 12 pans 20 mm |
| MS86 21 | 21 mm | 110 | Douille femelle isolée 3/8" 12 pans 21 mm |
| MS86 22 | 22 mm | 120 | Douille femelle isolée 3/8" 12 pans 22 mm |
| MS86 23 | 23 mm | 130 | Douille femelle isolée 3/8" 12 pans 23 mm |
| MS86 24 | 24 mm | 140 | Douille femelle isolée 3/8" 12 pans 24 mm |
| MS86 3/4 | 3/4" | 70 | Douille femelle isolée 3/8" 12 pans 3/4" |
| MS86 3/8 | 3/8" | 40 | Douille femelle isolée 3/8" 12 pans 3/8" |
| MS86 5/16 | 5/16" | 35 | Douille femelle isolée 3/8" 12 pans 5/16" |
| MS86 5/8 | 5/8" | 50 | Douille femelle isolée 3/8" 12 pans 5/8" |
| MS86 7/16 | 7/16" | 40 | Douille femelle isolée 3/8" 12 pans 7/16" |

| Product reference | Diámetro | Peso (g) | Désignation |
|-------------------|----------|----------|---|
| MS86 7/8 | 7/8" | 120 | Douille femelle isolée 3/8" 12 pans 7/8" |
| MS86 9/16 | 9/16" | 45 | Douille femelle isolée 3/8" 12 pans 9/16" |