

/ PA3GTI



Ver la ficha técnica  
en línea






/ Normas

- CEI 61230

/ Ventajas

- Installation of a very high ground malt from the ground level
- System that facilitates the installation of malt
- Ensures effective contact with the cable









/ Areas de actividad

-  Distribución de electricidad
-  Protección civil
-  Transporte

## / Características

- Product kind : Dispositif
- Operating voltage (V) : HTA (1 000 V to 50 000 V)
- Field of use (environment) : Aerial or transformation station
- In line (aerial) : Isolated
- Way of access : From the floor
- Short-circuit intensity kA/1s : 8
- Measurement : 2700x1000x10mm
- Weight (kg) : 28

## / Accesorios

	Referencia	Designación
	NE12	NE11 gripper tip
	NE28	Insulated pole maintenance kit
	NE18ER	Complementary extension
	NE14	Self-locking clamp
	NE22	Winding reel not wired
	NE25	1 set of 3 braids 35mm <sup>2</sup> , length 10m
	NE27	Maintenance kit for telescopic metal poles
	NE21ALU	Winding reel with aluminium cables and earth clamp

## / Productos contenidos en el kit

	Referencia	Designación
	NE18E	Lower part of insulating pole
	NE10	Telescopic metal poles
	NE20	Guide tulip
	701	Hexagonal ground rod.
	NE19E	Lower extension for insulating pole
	NE17E	Top part of insulating pole
	NE21	Cable reel with copper cables and grounding clamp
	NE24	NEVERS carrying case