



Ver la ficha técnica
en línea

/ TE41AUD

Lightweight rolling individual platform in fibreglass and aluminium



/ Normas

EN 131-7

/ Uso

Automatically opening ultra-light model designed to replace stepladders and combination ladders, but with a safe work platform and adjustable legs to adapt to level differences (pavements, steps). Particularly suited to work at low heights in urban environments.

/ Características

Patented platform opening/closing system : the two front legs that offer stability can be opened and positioned in a single movement.

420 x 480 mm floor with openings for better adherence.

Pivoting swing gate for a safe and easy access.

Uprights and adjustable legs made of composite fibreglass polyester : non-conductive and non-staining.

Floor and swing gates made of aluminium.

Flat rungs.

Tool holder injected in the handrail.

Product reference	Poids (kg)	Nombre d'échelons	Weight (kg)	Ht plateforme (m)	Amplitude de travail (m)	Working height (m)	Platform height (m)	Encombrement (m)
TE41AUD1,86M	12	2	-	0,50	1,50 / 2,20	-	-	1,86 x 0,75 x 0,22
TE41AUD2,14M	-	3	13	-	-	1,75 / 2,45	0,75	2,14 x 0,75 x 0,22
TE41AUD2,42M	-	4	14	-	-	2 / 2,7	1	2,42 x 0,75 x 0,22