



Ver la ficha técnica
en línea

/ MTAG

Detector de tensión 1 - 69 kV



/ Normas

- IEC 61243-1: VOLTAGE DETECTORS CAPACITIVE TYPE TO BE USED FOR VOLTAGES EXCEEDING 1 kV A.C
- Conformidad CE

/ Uso

Estos detectores de tensión están diseñados para verificar que una tensión nominal está efectivamente ausente de un circuito en un sistema de AT entre 1 kV y 69 kV (Verificación de Ausencia de Tensión) :

- El aparato debe detectar cualquier tensión nominal presente en una red o en una subestación.
- Evita detectar las tensiones inducidas para poder realizar las operaciones de puesta a tierra.

/ Ventajas

- Loud indication sound (the 100 dB at 1m)
- The visual indication is visible in all positions
- Direct access to the battery and sealed electronics compartment (IP65)
- Permanent standby status with automatic wake up function
- The presence of voltage within the calibrated range or above is indicated by a RED light and a beeping sound
- Self test OK the OK status (ready for use) of the device is indicated by a GREEN light
- The self test checks all the circuits, the reference detection level and the battery voltage
- The "ready for use" state is indicated by the green indication for 2 minutes
- A low battery level is indicated by an ORANGE light
- Removable and interchangeable stick end fitting

/ Areas de actividad

- | | |
|---|--|
|  Distribución de electricidad |  Sub-estaciones |
|  Industria |  Tracción eléctrica |
|  Generación |  Transporte |

/ Características

- Power type : Alternating power
- Network frequency (Hz) : 50/60
- Condition of use : Inside, Outside
- Temperatura de funcionamiento (C°) : -25...+55
- Humedad (máx.) (%) : 96
- Battery type : 9V battery (x1)
- Material de la carcasa : Policarbonato
- Color : Yellow
- Measurement (mm) : 280 x 59 x 59
- Weight (kg) : 0.390
- Nivel de señal acústica : 100 dB



Acceso pila



Indicación de presencia de una
tensión / Sin indicación de voltaje



Fonda metalizada Con protección
electromagnética CEM/Caja
metálica

/ Accesorios

	Referencia	Designación
	Les perches conformes à la CEI60855-1 et CEI61235	TUBOS AISLANTES