



Ver la ficha técnica
en línea

/ HTAG

Detector de tensión 50-765 kV



/ Normas

- IEC 61243-1: VOLTAGE DETECTORS CAPACITIVE TYPE TO BE USED FOR VOLTAGES EXCEEDING 1 kV A.C
- Conformidad CE

/ Uso

Estos detectores de tensión están diseñados para comprobar que una tensión nominal está realmente ausente de un circuito en un sistema de AT entre 50 kV y 765 kV (Comprobación de ausencia de tensión) :

- El aparato debe detectar cualquier tensión nominal presente en una red o en una subestación.
- Evita detectar las tensiones inducidas para poder realizar las operaciones de puesta a tierra.

/ Ventajas

- Loud indication sound (the 100 dB at 1m)
- The visual indication is visible in all positions
- Direct access to the battery and sealed electronics compartment (IP65)
- Permanent standby status with automatic wake up function
- The presence of voltage within the calibrated range or above is indicated by a RED light and a beeping sound
- Self test OK the OK status (ready for use) of the device is indicated by a GREEN light
- The self test checks all the circuits, the reference detection level and the battery voltage
- The "ready for use" state is indicated by the green indication for 2 minutes
- A low battery level is indicated by an ORANGE light
- Removable and interchangeable stick end fitting

/ Areas de actividad

-  Generación
-  Sub-estaciones
-  Transporte

/ Características

- Power type : Alternating power
- Network frequency (Hz) : 50/60
- Condition of use : Outside
- Temperatura de funcionamiento (C°) : -25...+55
- Humedad (máx.) (%) : 96
- Battery type : 9V battery (x1)
- Material de la carcasa : Policarbonato
- Measurement (mm) : 225 x 80 x 80
- Weight (kg) : 0,618
- Nivel de señal acústica : 100 dB



Acceso pila



*Indicación de presencia de una
tensión / Sin indicación de voltaje*



Fonda metalizada

/ Table legend

Otros adaptadores de polos disponibles bajo pedido.
Versión con caja metálica disponible previa solicitud.

Product reference	Rango de tensión (kV)	Connector type	Electrode type (mm)	Color	Notice	Packaging
HTAG060090FC	60-90	Universal (U), EAM	AC60, AC120, D100	Yellow	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG060090GC	60-90	Universal (U), EAM	AC60, AC120, D100	Yellow	PACK G (GB/GR/NL/BG/IT/AR/TR)	Metal case
HTAG060132FC	60-132	Universal (U), EAM	AC60, AC120, D100	Yellow	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG060150FC	60-150	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG060154FC	60-154	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG060220GC	60-220	Universal (U), EAM	AC60, AC120, D100	Red	PACK G (GB/GR/NL/BG/IT/AR/TR)	Metal case
HTAG060235FC	60-235	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG066132FC	66-132	Universal (U), EAM	AC60, AC120, D100	Yellow	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG066132G	66-132	Universal (U), EAM	AC60, AC120, D100	Yellow	PACK G (GB/GR/NL/BG/IT/AR/TR)	Without
HTAG069230FC	69-230	Universal (U), EAM	AC60, AC120, D100	Yellow	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG070220FC	70-220	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG088275FC	88-275	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG090225GC	90-225	Universal (U), EAM	AC60, AC120, D100	Red	PACK G (GB/GR/NL/BG/IT/AR/TR)	Metal case

Product reference	Rango de tensión (kV)	Connector type	Electrode type (mm)	Color	Notice	Packaging
HTAG110110G5C	110	Universal (U), EAM	AC60, AC120, D100	Red	PACK G (GB/GR/NL/BG/IT/AR/TR)	Metal case
HTAG110150FC	110-150	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG110220FC	110-220	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG110230FC	110-230	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG110230GC	110-230	Universal (U), EAM	AC60, AC120, D100	Red	PACK G (GB/GR/NL/BG/IT/AR/TR)	Metal case
HTAG110330F5C	110-330	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG115400FC	115-400	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG125125F5C	125	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG132220FC	132-220	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG150275FC	150-275	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG180540F5C	180-540	Universal (U), EAM	AC120, AC200	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG220330FC	220-330	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG220400FC	220-400	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG220400GC	220-400	Universal (U), EAM	AC60, AC120, D100	Red	PACK G (GB/GR/NL/BG/IT/AR/TR)	Metal case
HTAG225225F5C	225	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG066220FC	66-220	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case

Product reference	Rango de tensión (kV)	Connector type	Electrode type (mm)	Color	Notice	Packaging
HTAG090225FC	90-225	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG220420FC	220-420	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG220500FC	220-500	Universal (U), EAM	AC60, AC120, D100	Red	PACK F (FR/GB/DE/ES/PT/PL)	Metal case
HTAG060154GC	60-154	Universal (U), EAM	AC60, AC120, D100	Red	PACK G (GB/GR/NL/BG/IT/AR/TR)	Metal case