



Vedi scheda  
prodotto online

## / CS-KA

Lucchetto di blocco con grillo intercambiabile - a chiave uguale



### / Utilizzo

For lockout procedure following the 5 lockout-tagout steps.

Key system : keyed alike

With numbered key system, and tracking. Only a key with a number identical to the padlock allows its opening. The same key can open a set of padlocks with the same number, thus simplifying the management of keys on a site.

### / Specifiche tecniche

- Non-metallic body padlock, with the possibility of 9 interchangeable shackles, to be chosen when ordering.
- Shackles available in 2 materials: metal or composite, in 2 heights: 38 or 76 mm, and in 3 diameters: 4.5 mm or 6 mm or 1 mm sheathed cable shackle.
- Key system : keyed alike, only a key with a number identical to the padlock allows its opening.
- 8 colours available.
- Padlock dimensions without shackle : 54 x 46 x 21 mm
- Padlock weight without shackle and key : 80 g
- Delivered with a mounted shackle (of your choice) + 1 key + 1 set of lockout tags in 6 languages (abrasion and UV resistant) + 1 instruction manual.

### / Legenda della tavola

Sostituire il numero di riferimento con il numero di chiave richiesto (4 cifre). Per un numero specifico, contattateci. Sostituire il riferimento x con il codice colore richiesto (da 1 a 8): arancione (1), rosso (2), blu (3), verde (4), giallo (5), marrone (6), bianco (7), nero (8).

### Vantaggi

• **Interchangeable shackle system**

This exclusive feature allows the quick adaptation of the shackle to the installation to lock out without needing to change the padlock.

We offer 7 different shackles that adapt to all our padlocks:

- Height 36 or 72 mm
- Metal or composite material
- 4.5 mm or 6 mm diameter or ultra-thin Ø 1 mm cable

• **High security keys**

- Keys combining punches and grooves to high security levels
- Over 1.000.000 possible blade profile variations
- Captive key system: it is impossible to remove the key if the padlock is not locked
- Automatic return cylinder

Riferimento del prodotto	Ansa	diametro dell'ansa (mm)	Altezza del ansa (mm)
CS-KA#-x-F1	corda metallica con manicotto in vinile	1	70
CS-KA#-x-M438	Metallo	4,5	38
CS-KA#-x-M476	Metallo	4,5	76
CS-KA#-x-M638	Metallo	6	38
CS-KA#-x-M676	Metallo	6	76
CS-KA#-x-P438	composito	4,5	38
CS-KA#-x-P476	composito	4,5	76
CS-KA#-x-P638	composito	6	38
CS-KA#-x-P676	composito	6	76