

/ DR706IVNEU

Indicatore dell'ordine di fase



Vedi scheda
prodotto online






/ Standard

- IEC 61557-7
- Categoria di protezione : IV-600 V
- Conformità CE

/ Vantaggi

- Intelligent display. A slow LED chaser reproduces the rotation of a motor. The GREEN clockwise direction and the RED anticlockwise direction make it easier to memorise the initial condition.
- A shape designed to fit in the hollow of the palm.
- All the functions are available while wearing insulating gloves.
- Works on generating sets.
- Simple use: No setup or adjustment. Operates without batteries.
- A heavy duty housing that is fully sealed.
- Replaceable leads with European colour codes and L1 L2 L3 marking (Other markings or colours to order).
- Adaptability: May be used with a number of accessories for systems (Crocodile clips, touch tips, with or without fuses and leads with or without fuses).

/ Settori di attività

-  Cavi e connettori
-  Distribuzione di elettricità
-  Industria

/ Specifiche tecniche

- Tipo di tensione : Tensione alternativa
- Frequenza di rete : 50-60 Hertz
- Intervallo di tensione (kV) : 80-400
- Condizioni di utilizzo : Interno, Esterno
- Temperatura di esercizio (C°) : -10...+55
- Umidità (massima) (%) : 96
- Tightness protection : IP65
- Materiale della custodia : ABS
- Colore : Nero
- Misura (mm) : 120 x 75 x 27
- Peso (kg) : 0,2
- Tipo di cavo : Silicone
- Lead length (mm) : 1000
- Leads colors : Brown, Black, Grey
- Probes : Retractable sleeve
- Foglio informativo : Multilingual

