



Çevrimiçi veri
sayfasına bakın

/ E06 2KGS

ABC powder fire extinguisher, capacity 2 kg



/ Standards

In conformity with the Pressure Equipment Directive PED97/23/EC, MED96/98/EC and CEN EN3

/ Use

Suitable for all fires (except metal fires).

May be used on live electrical networks with nominal voltage below 1000 V AC.

Fire classes : A13 - B89 - C

/ Technical specifications

Stored pressure, multi-purpose dry powder fire extinguisher with pressure gauge:

- Body : Single piece, deep drawn aluminium alloy body, externally painted with polyester resin.
- Valve : The handy compact valve is ergonomically designed to guarantee an easy use with one hand. A pressure gauge is provided. All external parts are either in plastic material or protected against corrosion.
- Propellant : The propellant gas is nitrogen. A small percentage of helium is added, to facilitate electronic leak detection.
- Extinguishing agent : ABC multi-purpose dry powder. All parts in contact with the extinguishing agent are compatible with the same.
- Bracket : Plastic bracket specially designed for vehicle and marine use.

Operating temperature range: -30°C / + 60°C

Fire classes: 13A - 89B - C

Advantages

Light aluminium alloy body.
Manometer for pressure control.
Plastic bracket with luminescent strip for an easy location in the dark.