



Çevrimiçi veri
sayfasına bakın

/ Série MIT400

Insulation and continuity testers



/ Standards

IEC 61326-1

/ Technical specifications

- CATIV 600V applications
- Insulation testing to 1000V and to 200G Ω
- TRMS & DC Voltage measurement
- Continuity testing at 200mA down to 0.01 Ω
- Analogue and dual digital display
- Insulation & continuity limit alarms
- PI/DAR and Timer function
- Test result storage
- Bluetooth wireless data transfer
- Free calibration certificate included
- Supplied with case and leads
- 3 Year warranty
- Power Supply : 5 x 1.5 V AA batteries
- Dimensions : 220 x 92 x 50 mm
- Weight : 775 g

Advantages

Waisted profile makes it easily held by operators with the smallest hands
Can be used right or left-handed

Product reference	Fonction supplémentaire	Gamme de résistance d'isolement	Tensions de test nominales
MIT400	-	20 G Ω	250, 500, 1000 V
MIT410	PI and DAR	100 G Ω	50 ,100, 250, 500, 1000 V
MIT415	-	50 G Ω	10, 25, 50, 100, 250, 500 V
MIT420	Results storage and recall	200 G Ω	50 ,100, 250, 500, 1000 V
MIT430	Results storage and recall, bluetooth transfer	200 G Ω	50 ,100, 250, 500, 1000 V
MIT480	-	100 G Ω	50, 100 V
MIT481	Result storage	200 G Ω	50 ,100, 250, 500, 1000 V