

/ XC25W

Çevrimiçi veri
sayfasına bakın

	TYPE DE CÂBLES	DURETÉ MAX.	Ø MAX. DE COUPE *
CÂBLES MULTI-TORONS	1" x 10 torons - acier	150 > 160 daN/mm ²	Ø 16 x 16 mm
	2" x 37 torons - acier	150 > 160 daN/mm ²	Ø 12 x 13 mm
CÂBLES ELECTRIQUES	Alu - aluminium		Ø 20 mm
	Alu - aluminium - galvanisé		Ø 20 x 22 mm
	Alu - aluminium - galvanisé - zinc		Ø 20 x 22 mm
BÂTTES CYLINDRIQUES	Alu - aluminium	< 20 daN/mm ²	Ø 10 x 22 mm
	Alu - aluminium	20 > 20 daN/mm ²	Ø 10 x 22 mm
	Alu - aluminium	< 20 daN/mm ²	Ø 10 x 25 mm
	Alu - aluminium	40 > 40 daN/mm ²	Ø 12 x 14 mm
	Alu - aluminium	60 > 70 daN/mm ²	Ø 15 mm
CÂBLES ISOLES	Alu - aluminium	150 > 160 daN/mm ²	Ø 16 x 16 mm
	Alu - aluminium	< 150 daN/mm ²	Ø 16 x 16 mm

* Autres dimensions et câbles à valider sur essais.

/ Özellikler

- Tools king : Specific tools

