



Çevrimiçi veri
sayfasına bakın

/ MTAG0104FHUA

MTAG gerilim dedektörü



/ Standartlar

- IEC 61243-1: VOLTAGE DETECTORS CAPACITIVE TYPE TO BE USED FOR VOLTAGES EXCEEDING 1 kV A.C
- CE uyumlu

/ Kullanım

Bu voltaj dedektörleri, 1 kV ile 69 kV arasındaki bir H.T. sistemindeki bir devrede nominal bir voltajın etkin bir şekilde bulunmadığını doğrulamak için tasarlanmıştır (Voltaj Yokluğu Doğrulaması):

- Cihaz, bir şebekede veya bir trafo merkezinde mevcut olan herhangi bir nominal gerilimi tespit etmelidir.
- Topraklama işlemlerinin gerçekleştirilebilmesi için indüklenmiş gerilimleri tespit etmekten kaçınır.

/ Avantajlar

- Loud indication sound (the 100 dB at 1m)
- The visual indication is visible in all positions
- Direct access to the battery and sealed electronics compartment (IP65)
- Permanent standby status with automatic wake up function
- The presence of voltage within the calibrated range or above is indicated by a RED light and a beeping sound
- Self test OK the OK status (ready for use) of the device is indicated by a GREEN light
- The self test checks all the circuits, the reference detection level and the battery voltage
- The "ready for use" state is indicated by the green indication for 2 minutes
- A low battery level is indicated by an ORANGE light
- Removable and interchangeable stick end fitting

/ Faaliyet alanları

- | | | | |
|--|-------------------|---|-------------------|
|  | Elektrik dağıtımı |  | Trafo Merkezi |
|  | Endüstri |  | Elektrikli tahrik |
|  | Üretim |  | Nakliye |

/ Özellikler

- Power type : Alternating power
- Network frequency (Hz) : 50/60
- Gerilim aralığı (kV) : 1-4
- Condition of use : Inside, Outside
- Çalışma sıcaklığı (C°) : -25...+55
- Nem (Maks.) (%) : 96
- Battery type : 9V battery (x1)
- Connector type : Universal (U), APV
- Electrode type (mm) : V56
- Gövde malzemesi : Polikarbonat
- Color : Yellow
- Measurement (mm) : 280 x 59 x 59
- Weight (kg) : 0.390
- Akustik sinyal seviyesi : 100 dB
- Notice : PACK F (FR/GB/DE/ES/PT/PL)
- Packaging : Soft case with conductive lining for EMC protection

